

B2 to the hinged part can be pressed against the windshield to be wiped by a spring element that is mounted on the four-hinged wiper arm, wherein one of the connecting rod, the driving arm, and the control arm is provided with a rolling-contact bearing in at least one of the first and second bearing points of the four-hinged wiper arm.

B3 12. (Amended) The four-hinged wiper arm according to claim 9 characterized in that an outer ring of the at least one rolling-contact bearing is axially secured and held, so that it does not rotate in one recess of the connecting rod whereas a bolt, attached to one of the driving arm and the control arm, is fitted into an inner ring of the rolling-contact bearing and is axially secured and non-rotatably held.

B4 14. (Amended) The four-hinged wiper arm according to claim 13, characterized in that the riveted bolt is secured by wobble riveting in a passage one of the driving arm and control arm, and by wobble riveting at the inner ring of the rolling-contact bearing.

B5 16. (Amended) The four-hinged wiper arm according to claim 9, further comprising a rolling-contact bearing with a deep groove ball bearing both at the first bearing point between the connecting rod and the driving arm and at the second bearing point between the connecting rod and the control arm.

Please add the following new claims:

B6 17. (New) In a four-hinged wiper arm for a windshield wiper, having a connecting rod pivotally connected to a driving arm at a first bearing point on the connecting rod and to a control arm at a second bearing point on the connecting rod and a hinged part coupled to the connecting rod and a wiper rod connected to the hinged part for pressing against the windshield to be wiped by a spring element mounted on the four-hinged wiper arm, the improvement comprising:

a rolling-contact bearing provided with one of the connecting rod and driving arm in at least one of the first and second bearing points of the four-hinged wiper arm.

18. (New) The improvement according to claim 17, wherein at least one of the rolling-contact bearings is a deep groove ball bearing.

19. (New) The improvement according to claim 17 wherein the driving arm and the control arm are made of sheet metal.

20. (New) The improvement according to claim 17 wherein the rolling-contact bearing has an inner and outer ring and that the outer ring of the at least one rolling-contact bearing is axially secured and held, so that it does not rotate in one recess of the connecting rod whereas a bolt, attached to one of the driving arm and the control arm, is fitted into the inner ring of the rolling-contact bearing and is axially secured and non-rotatably held.

21. (New) The four-hinged wiper arm according to claim 20 wherein the bolt used on the at least one first and second bearing point is a riveted bolt.

22. (New) The improvement according to claim 21, wherein the riveted bolt is secured by wobble riveting in a passage in one of the driving arm and control arm, and by wobble riveting at an inner ring of the rolling-contact bearing.

23. (New) The improvement according to claim 22, wherein the riveted bolt has a radially protruding flange in a middle region, with one side that rests against one of the driving arm and the control arm, and another side that rests against a front surface of the inner ring of the rolling-contact bearing.

24. (New) The improvement according to claim 17, further comprising a rolling-contact bearing with a deep groove ball bearing both at the first bearing point between the connecting rod and the driving arm and at the second bearing point between the connecting rod and the control arm.

---

B6